CLAIMS

1. A target detection system comprising:

     a radar;

     an image acquisition unit; and

     a processing unit for specifying an area
of image recognition based on the data output from said
radar and processing the image data output from said
image acquisition unit only for said specified area.

2. A target detection system comprising:

     a radar for scanning a specified area and
outputting signal of power corresponding to an object
scanned;

     an image acquisition unit for acquiring an
image of said specified area; and

     a processing unit for specifying an area
of image recognition based on the power of the signal
output from said radar, extracting the edge data from the
image data output from said image acquisition unit only
for said specified area, and detecting a target based on
said edge data.

3. A target detection system according to claim 2,
     wherein said processing unit specifies an
area having said power not less than a predetermined
level as said image recognition area.

4. A target detection system according to claim 2,
     wherein said processing unit specifies an
area having said power between a first predetermined
level and a second predetermined level as said image
recognition area.

5. A target detection system according to claim 2,
     wherein, in the case where the level of
said power has a plurality of peaks, said processing unit
specifies an area constituting a valley between the peaks
as said image recognition area.

6. A target detection system according to claim 2,
     wherein said processing specifies as said
image recognition area an area having said power not less

than a predetermined level, an area having said power
between a first predetermined level and a second
predetermined level, and an area constituting a valley
between peaks in the case where the level of said power
5   has a plurality of peaks.

7.   A target detection system according to claim 2,
wherein said processing unit extracts the
peak position of the power of the signal output from said
radar, checks the density change, on the left and right
10 sides of said peak position, of the image data output
from said image acquisition unit, extracts the position
where the density change ceases to be laterally
symmetric, and specifies an area having a predetermined
width about said extraction position as said image
15 recognition area.

8.   A target detection system according to claim 2,
wherein said processing unit extracts the
peak position of the power of the signal output from said
radar, examines the density projection value, on the left
20 and right sides of said peak position, of the image data
output from said image acquisition unit, extracts the
position where the density projection value ceases to be
laterally symmetric, and specifies an area having a
predetermined width about said extraction position as
25 said image recognition area.

9.   A target detection system comprising:
a radar for scanning a specified area and
outputting signal of power corresponding to an object
scanned;
30 an image acquisition unit for acquiring an
image of said specified area; and
a processing unit for extracting the edge
data from the image data output from said image
acquisition unit, specifying an area of image recognition
35 based on the power of the signal output from said radar,
and detecting a target using those of said extracted edge
data existing in said specified area.

10. A target detection system according to claim 9, wherein said processing unit specifies an area having said power not less than a predetermined level as said image recognition area.

11. A target detection system according to claim 9, wherein said processing unit specifies an area having said power between a first predetermined level and a second predetermined level as said image recognition area.

12. A target detection system according to claim 9, wherein, in the case where the level of said power has a plurality of peaks, said processing unit specifies an area constituting a valley between the peaks as said image recognition area.

13. A target detection system according to claim 9, wherein said processing unit specifies, as said image recognition area an area having said power not less than a predetermined level, an area having said power between a first predetermined level and a second predetermined level, and an area constituting a valley between peaks in the case where the level of said power has a plurality of the peaks.

14. A target detection system comprising:
a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;
an image acquisition unit for acquiring the image of a specified area; and
an image recognition unit for outputting edge data by processing the image data output from said image acquisition unit;
a processing unit for determining the state of the near flag output from said radar and detecting a target based on the edge data in the distance range corresponding to the state of said near flag among the edge data output from said image recognition unit.

15. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

5 an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, removing and outputting the edge data in the distance

10 range corresponding to the state of the near flag output from a processing unit; and

a processing unit for determining the state of the near flag output from said radar, outputting the result thereof to said image recognition unit, and

15 detecting a target based on the edge data output from said image recognition unit.

 16. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination

20 that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said

25 image acquisition unit and, among said edge data, performing the pattern matching processing in priority for the edge data within the distance range corresponding to the state of the near flag output from a processing unit, and outputting said edge data; and

30 a processing unit for determining the state of the near flag output from said radar, outputting the result thereof to said image recognition unit, and detecting a target based on the edge data output from said image recognition unit.

35 17. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination

that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching the road surface flag to the edge data identified as an edge of the road surface from the height information and the distance information obtained from said image data; and

a processing unit for determining the distance range corresponding to the state of the near flag output from said radar, invalidating the edge data output from said image recognition unit and having said road surface flag attached thereto, in the case where the distance information of said edge data with said road surface flag attached thereto indicates a near distance and said determined distance range indicates a far distance, and performing said target detection process based on the remaining edge data.

18. A target detection system comprising:

a radar for outputting distance information;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching the road surface flag to the edge data identified as an edge of the road surface based on the height information and the distance information obtained from said image data; and

a processing unit for determining whether the distance information of the edge data output from said image recognition unit and having said road surface flag attached thereto is within the allowable error range of the distance information acquired from said radar, in

the case where said edge data with said road surface flag attached thereto indicates a far distance, and invalidates said edge data and performs the target detection process based on the remaining edge data in the case where said distance information is not within said allowable error range.

19. A target detection system comprising:

a radar for outputting a near flag in the state corresponding to the distance upon determination that a target exists in a near area;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching a letter flag to the edge data identified as a letter on the road surface based on the density information obtained from said image data; and

a processing unit for determining the distance range corresponding to the state of the near flag output from said radar, invalidating the edge data output from said image recognition unit and having said letter flag attached thereto in the case where the distance information of the edge data with said letter flag attached thereto indicates a near distance and said determined distance range indicates a far distance, and performing said target detection process based on the remaining edge data.

20. A target detection system comprising:

a radar for outputting distance information;

an image acquisition unit for acquiring the image of a specified area;

an image recognition unit for acquiring edge data by processing the image data output from said image acquisition unit and, among said edge data, outputting by attaching a letter flag to the edge data

identified as a letter on the road surface based on the
density information obtained from said image data; and

a processing unit for determining whether
the distance information of the edge data output from
said image recognition unit and having said letter flag
attached thereto is within the allowable error range of
the distance information acquired from said radar, in the
case where said distance information of the edge data
with said letter flag attached thereto indicates a far
distance, and invalidating said edge data and performing
the target detection process based on the remaining edge
data in the case where said distance information is not
within said allowable range.

21. A target detection system comprising:

a radar for outputting a near flag in the
state corresponding to the distance upon determination
that a target exists in a near area;

an image acquisition unit for acquiring
the image of a specified area;

an image recognition unit for acquiring
edge data by processing the image data output from said
image acquisition unit and, among said edge data,
outputting by attaching a road surface flag to the edge
data identified as a letter on the road surface based on
the height information and the distance information
obtained from said image data, and also by attaching a
letter flag to the edge data identified as a letter on
the road surface based on the density information; and

a processing unit for determining the
distance range corresponding to the state of the near
flag output from said radar, and invalidating the edge
data output from said image recognition unit and having
at least one of said road surface flag and said letter
flag attached thereto, in the case where the distance
information of said edge data having at least one of said
road surface flag and said letter flag attached thereto
indicates a near distance and said determined distance

range indicates a far distance, and performing said
target detection process based on the remaining edge
data.

22. A target detection system comprising:

5   a radar for outputting a near flag in the
state corresponding to the distance upon determination
that a target exists in a near area;

                an image acquisition unit for acquiring
the image of a specified area;

10   an image recognition unit for acquiring
edge data by processing the image data output form said
image acquisition unit and, among said edge data,
outputting by attaching a road surface flag to the edge
data identified as a letter on the road surface based on

15   the height information and the distance information
obtained from said image data and also by attaching a
letter flag to the edge data identified as a letter on
the road surface based on the density information; and

                a processing unit for determining whether

20   the distance information of the edge data output from
said image recognition unit and having at least one of
said road surface flag and said letter flag attached
thereto is within the allowable error range of the
distance data obtained from said radar, in the case where

25   the distance information of said edge data having at
least one of said road surface flag and said letter flag
attached thereto indicates a far distance, and
invalidating said edge data having at least one of said
road surface flag and said letter flag attached thereto

30   and performing said target detection process based on the
remaining edge data, in the case where said distance
information is not within said allowable error range.